



STANDARD.

- UL STANDARD (FILE No.: E81260)
- CSA STANDARD (FILE No. : LR 76687)
- STANDARD PRODUCT
- NC : WITH SILICONCE LUBRICATION
- SNC : NON-SILICONCE

MATERIALS.

- NTT 108 (GENERAL)
- IM-104/No.4 (UL AND CSA)
- EX-724 (HIGH TEMP)

COLORS.

- B = BLACK, L = BLUE, G = GREEN, R = RED, W = WHITE, Y = YELLOW

Cat No. 8

UNIT : MM.

PART No.	ØD	L		T		PACKING (PCS)
		(STD.)	(MAX.)	(General)	(UL/CSA)	
		±1.5		±0.3	+0.3/-0.2	
NC1.5	1.5	15.0	15.0	0.8	1.0	1,000
NC2.0	2.0	15.0	15.0	0.8	1.0	1,000
NC2.5	2.5	15.0	15.0	0.8	1.0	1,000
NC3.0	3.0	15.0	20.0	0.8	1.0	1,000
NC3.5	3.5	15.0	20.0	0.8	1.0	1,000
NC4.0	4.0	15.0	20.0	0.8	1.0	1,000
NC4.5	4.5	15.0	20.0	0.8	1.0	1,000
NC5.0	5.0	15.0	30.0	0.8	1.0	1,000
NC5.5	5.5	15.0	30.0	0.8	1.0	1,000
NC6.0	6.0	15.0	30.0	0.8	1.0	1,000
NC6.5	6.5	15.0	30.0	0.8	1.0	1,000
NC7.0	7.0	15.0	30.0	0.8	1.0	500
NC7.5	7.5	15.0	30.0	0.8	1.0	500
NC8.0	8.0	15.0	30.0	1.0	1.0	500
NC8.5	8.5	15.0	30.0	1.0	1.0	500
NC9.0	9.0	15.0	30.0	1.0	1.0	500
NC9.5	9.5	15.0	30.0	1.0	1.0	500
		±1.5		±0.3	+0.3/-0.2	
NC10.0	10.0	20.0	30.0	1.0	1.0	500
NC10.5	10.5	20.0	30.0	1.0	1.0	500
NC11.0	11.0	20.0	30.0	1.0	1.0	500
NC11.5	11.5	20.0	30.0	1.0	1.0	500

PART No.	ØD	L		T		PACKING (PCS)
		(STD.)	(MAX.)	(General)	(UL/CSA)	
		±1.5		±0.3	±0.3	
NC12.0	12.0	20.0	30.0	1.2	1.2	500
NC12.5	12.5	20.0	30.0	1.2	1.2	500
NC13.0	13.0	20.0	30.0	1.2	1.2	500
NC14.0	14.0	20.0	30.0	1.2	1.2	500
NC14.5	14.5	20.0	30.0	1.2	1.2	500
		±2.0		±0.3	±0.3	
NC15.0	15.0	20.0	30.0	1.2	1.2	500
NC15.5	15.5	20.0	30.0	1.2	1.2	500
NC16.0	16.0	20.0	30.0	1.2	1.2	500
		±2.0		±0.5	±0.5	
NC18.0	18.0	25.0	30.0	1.5	1.5	100
NC19.0	19.0	25.0	30.0	1.5	1.5	100
NC20.0	20.0	25.0	30.0	1.5	1.5	100
NC21.0	21.0	25.0	30.0	1.5	1.5	100
NC22.0	22.0	25.0	40.0	1.5	1.5	100
NC24.0	24.0	25.0	40.0	1.5	1.5	100
NC28.0	28.0	30.0	40.0	1.5	1.5	100
NC32.0	32.0	30.0	40.0	1.5	1.5	100
		±3.0		±0.5	±0.5	
NC38.0	38.0	40.0	50.0	1.5	1.5	50
NC44.0	44.0	40.0	50.0	1.5	1.5	50
NC75.0	75.0	50.0	50.0	1.5	1.5	50

REMARK :

1 2 X 3 X 4 5

EX. NC 3.5 X 15.0 X 0.8 B

- 1 : NC = NORMAL PART , SNC = NON SILICONE PART
- 2 : DIAMETER (EX. 3.5)
- 3 : LONG (EX.15.0)
- 4 : THICKNESS (EX. 0.8)
- 5 : COLOUR (B = BLACK)